# **7818** HIGH TEMPERATURE GREASE

**Chemico 7818** is a multi-use barrier coating that can with stand temperatures up to 325° Fahrenheit, when placed on vertical surfaces this product will not sag. 7818 reduces airborne particulates and is very visible with its' red color. This product is especially useful in hard to reach areas that collect dirt that could become air borne, because of its' staying power.

### **PRODUCT APPLICATION**

- Use in high temperature areas were other booth greases will sag or smoke.
- Use under conveyors or other hard to reach areas in clean rooms.

#### **TECHNICAL DATA**

- Physical State: Solid
- Color: Dark Red
- Odor: Petroleum Like
- Specific Gravity (H<sub>2</sub>O=1.00): 0.92 (a) room temperature (68°F)
- Typical pH: NA
- VOC Content: 0 lbs./gallons

## **DIRECTIONS FOR USE**

**Chemico 7818** can be manually applied by roller or brush. A uniform application of approximately 5 mils will ensure a more consistent performance. This product can be placed on aluminum foil that is secured to the surface with magnets or applied directly to steel surfaces. You can remove the aluminum foil or scrape product directly off the sub-straight. Recoat over residual 7818 or remove 100% by washing the area with a water-based degreaser, Chemico 6917E is a cleaner that will remove grease and is paint shop friendly.

## SAFETY

Contact your Chemico representative for additional product information and always review the SDS – Safety Data Sheets before using this or any Chemico product.